

Take Advantage of the Benefits



- Our ESD tile delivers all of the ergonomic benefits of our standard anti-fatigue product while providing industry leading ESD performance.
- Through our proprietary manufacturing process, Ergo Advantage ESD tiles retain the required ESD performance through the full volume of the tile as compared to other mats that only offer “surface resistivity”.
- Aluminum or Copper Tape can be used as the grounding agent when installed over a non-grounded floor.
- The advanced Versatile Interlock System allows for ease and efficiency during installation and future modifications.
- Manufactured with 100% Recycled PVC for waste reduction.



Ergo Advantage ESD Closed Tile

Following strict quality control of our manufacturing process each tile delivers consistent ESD performance:

Surface Resistivity: $3 \times 10^6 - 3 \times 10^7$ Ohm

Volume Resistivity: $3 \times 10^6 - 3 \times 10^7$ Ohm

Test Procedure: ANSI/ESD S7.1

Custom resistivity performance within the dissipative range is also available. Minimum quantities apply.

Durometer:	Dimensions:	Weight:	Composition:	Warranty:
Shore Hardness “A” 85 (+/- 5)	Tile – 18” x 18” x 1” (2.25 sq.ft / tile)	5.5 lbs	100% Recycled/ Recyclable PVC	Unprecedented 20 year warranty